

06897 SIP SUB 3030-SS Heavy-Duty Dirty Water Pump



Part No: 06897

Price: £99.99 (exc VAT) Save £61.01 (RRP £161.00) | £119.99 (inc VAT)

Specifications

06897 SIP SUB 3030-SS Heavy-Duty Dirty Water Pump

The SIP SUB 3010-SS Heavy-Duty Dirty Water Pump is ideal for draining dirty water from work areas and ditches, water tanks or vessels and large ponds.

The pump is suited for heavy-duty use as a temporary or permanent fixture.

Water pumps can help prevent costly damage to property or work areas from recurring rainwater or groundwater.

This pump can also be used for a variety of agricultural and construction purposes.

Features

Powerful 1kW/1.3hp brushless induction motor

Fitted float switch prevents pump from running dry

Max. 9mtr pumping head for quick draining

Drains dirty water with particles up to Ø 35mm

Lightweight and compact design

SIP 2-Year Standard Silver Warranty

Applications & uses: Quickly drains flooded areas.

Suitable for agricultural or construction environments.

Designed as a temporary or permanent fixture.

Powerful brushless induction motor (1kW/1.3hp)

Draws water at a max. flow rate of 300ltr/min through an impeller at the pump base. The heavy-duty wound motor is durable and lightweight.

Fitted float switch

Ensures the pump functions unaided when the activation depth (450mm) is reached.

This prevents the pump from running dry and overheating when in use.

Max. 9mtr pumping head

Discharges water flow to a max. height of 9mtr through hose or pipe connected to the pump outlet.

This ensures the intended area or item is drained quickly.

Particle capacity

Suitable for draining dirty water with particles to max. diameter of 35mm.

Lightweight, compact design

Includes a carry handle for portability and lowering into water (7mtr max. operating depth).

A mounted power cable hook provides added safety.

Stainless steel housing

Hard-wearing, durable casing ensures it withstands the demanding environments it is intended for.

High-grade carbon steel pump shaft

High-tensile strength compound for long life use.

Power cable

Fitted with a 10mtr length cable for greater versatility.

Specifications

Input Supply: 230v 50Hz

Motor Power: 1kW (1.3hp)

Flow Rate: 300ltr/min

Outlet: 25mm Ø - 40mm Ø 1" BSP

Max. Pumping Head: 9mtr

Max. Operating Depth: 7mtr

Max. Particle Diameter: Ø 35mm

Max. Water Temperature: 35°C

Body Type: Stainless Steel

Pump Type: Dirty Water

Cable Length: 10mtr

Protection: IPX8