

Carpenter Goodwin
31 Bridge St
Leominster
Herefordshire
HR6 8DU
01568 616266
www.carpentergoodwin.co.uk

## MM20HV Digital 8 Function Multimeter Hi Vis



Part No: MM20HV

**Price:** £27.95 (exc VAT) | £33.54 (inc VAT)

## **Specifications**

MM20HV Digital 8 Function Multimeter Hi Vis with Thermocouple

Heavy-duty general purpose multimeter with clear and easy-to-read LCD display.

Features data hold function, temperature probe and diode test facility.

Housed in rugged rubber boot with integral stand.

Supplied with full set of leads and probes.

## Measures:

- AC and DC Voltage
- DC Current

22-12-2024 1/2

- Resistance

- Temperature

- Audible Continuity

- Diode/Transistor Verification Mode

Specification Table:

AC Voltage (Accuracy): 200V, 600V (±2%)

DC Voltage (Accuracy):  $200 \text{mV} (\pm 0.5\%)$ ,  $2 \text{V} (\pm 0.8\%)$ ,  $20 \text{V} (\pm 0.8\%)$ ,  $200 \text{V} (\pm 0.8\%)$ ,  $600 \text{V} (\pm 0.8\%)$ 

AC Current (Accuracy): No

DC Current (Accuracy): 2mA (±1%), 20mA (±1%), 200mA (±1.2%), 10A (±2%)

Resistance (Accuracy):  $200\Omega$ ,  $2k\Omega$ ,  $20k\Omega$ ,  $200k\Omega$  ( $\pm 0.8\%$ ),  $2M\Omega$  ( $\pm 1.2\%$ )

Capacitance (Accuracy): No

Temperature (Accuracy): Range;  $-40^{\circ}$ C- $1000^{\circ}$ C, ( $\pm 1\%$  up to  $400^{\circ}$ C), ( $\pm 2\%$  over  $400^{\circ}$ C)

Frequency (Accuracy): No

**Duty Cycle: No** 

Continuity Audible: Yes

Diode Test: Yes

Transistor Test: Yes

High-Impact Rubber Case: Yes

Digits x Height: 6 x 12mm

Low Battery Indicator: Yes

Battery (Supplied): 1 x 9V

Integral Stand: Yes

Size (L x W x D): 140 x 70 x 35mm

Conformity: IEC 1010

22-12-2024 2/2