

Suction/pressure hose 50mm



Part No: SL25050

Price: £5.51 (exc VAT) | £6.61 (inc VAT)

Specifications

| | |
|-------------------------------|--|
| Part number | SL25050 |
| Unit | metre |
| Specifications | <ul style="list-style-type: none"> • Wear-resistant, low weight • Very flexible |
| Benefits | <ul style="list-style-type: none"> • Long service life • Practical handling |
| Application | For pumping (waste) water and slurry |
| Properties | Ozone and UV resistant |
| Technical information | <ul style="list-style-type: none"> • suitable for towing hose distributors • flexible and soft |
| Type | Water hose |
| Material outside | PVC |
| Material inside | PVC |
| Reinforcement material | PVC |
| Reinforcement type | Coil |
| Colour outside | Green |
| Medium | <ul style="list-style-type: none"> • Water • Slurry |

| | |
|--------------------------------|---|
| Colour inside | <ul style="list-style-type: none">• Transparent• Green |
| Inside diameter | 50 mm |
| Outside diameter | 58.2 mm |
| Inside diameter | 2 Inch |
| Wall thickness | 4.1 mm |
| Max working pressure | 3.5 BAR |
| Burst pressure | 12 BAR |
| Max vacuum | 0.7 BAR |
| Max working temperature | 55 °C |
| Min working temperature | -25 °C |
| Bend radius | 200 mm |
| Weight | 0.81 kg/m |
| Length | 50 m |