

## Plug DN13-Ø16mm-WEO 1/2" 90°



**Part No:** WEO147140808

**Price:** £15.80 (exc VAT) | £18.96 (inc VAT)

### Specifications

WEO147140808 Plug DN13-Ø16mm-WEO 1/2" 90°

#### **Specifications**

- Innovative plug-in system with unthreaded connections
- Couple using only a screwdriver
- Low space requirement
- Coupled connections turn 360°

#### **Benefits**

- Time-saving
- Labour-saving
- Very simple handling
- No twisting of hoses when tightening

#### **Application**

- WEO fittings system bush inserts
- Front loaders
- Forklifts
- Lift gates
- Machines with tight installation space

|                                    |   |
|------------------------------------|---|
| <b>Properties</b>                  | <ul style="list-style-type: none"> <li>- Absolutely leak-proof</li> <li>- Longer hose service life</li> <li>- Free of Cr(III) and Cr(VI)</li> <li>- Safety factor at least: 4:1</li> <li>- TÜV certified</li> </ul> |
| <b>Technical information</b>       | <ul style="list-style-type: none"> <li>- A complete WEO coupling consisting of 1 bush insert and 1 plug</li> <li>- Suitable for 1 + 2 layers and 4SP hoses</li> </ul>   |
| <b>Unit</b>                        | Each  |
| <b>Material</b>                    | Steel   |
| <b>Surface treatment</b>           | Hardened  |
| <b>Temperature range (°C)</b>      | -30 <> +100   |
| <b>A (mm)</b>                      | 16  |
| <b>B (mm)</b>                      | 63  |
| <b>C (mm)</b>                      | 22  |
| <b>D (mm)</b>                      | 9.5   |
| <b>E (mm)</b>                      | 13.6  |
| <b>F (mm)</b>                      | 33  |
| <b>Hose diameter (mm)</b>          | 13.6  |
| <b>Max. working pressure (bar)</b> | 350   |

## Optional Extras

Clip 16mm-WEO 1/2"



**Part No:**  
WEO147490801  
**Price:**  
£0.91 (exc VAT)  
£1.09 (inc VAT)